



DUMBBELL SPECIFICATION

GSC01/45/8XX/YY

LM80,90 LED chips; universal voltage: 100-277V; excellent thermal design; aluminum die-casting housing; 0-10V dimming.

Product data

General Information

Light source replaceable	No
Number of gear units	1
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Optical cover/lens type	
Luminaire light beam spread	Flood
Sensor socket	•
Cable length	Cable 0.3m without plug
Protection class IEC	•
Certifications	cETLus, cULus, FCC, DLC5.0 Premium
Lifetime (hour)	50, 000H
EU RoHS compliant	Yes

Light source engine type	LED

Operating and Electrical

Input voltage	100-277V
Input frequency	50/60Hz
Current	0.5A
THD	<20%
Power factor (min)	0.9

Mechanical and Housing

Housing material	Aluminum
Reflector material	
Optical cover/lens material	Glass
Optical cover/lens finish	Clear
Product dimensions mm	325*325*288
Product dimensions (inch)	12.80*12.80*11.34
Product color	White

Approval and Application

Ingress protection code	65
Mech.impact protection code	

Initial Performance (IEC Compliant)

Light output	5400lm
Luminous flux to lerance	+/-10%
Efficacy	120/126 lm/w
Init.Corr.Color Temperature	3000K/4000K/5000K
Init.Color Rendering Index	80
Initial input power	45W
Power consumotion tolerance	+/-10%

Application Conditions

Ambient temperature range	-40 to +50°C
Dimming	0-10V

Logistical Data


Order product name	GSC01/45/8XX/YY
Net weight (piece)	•
Gross weight (piece)	•
Packaging dimensions (mm)	
Packaging dimensions (inch)	
Packaging unit (piece)	

Volumen (m³)	
Volumen (ft³)	

Application


Gas Station Lighting

Light Distribution & Spectrum



Flood(100 DEG)

Dimensional drawing



DUMBBELL I/S

Plusrite does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Plusrite. Plusrite is registered.