



ZEUS V SPECIFICATION

WPT05/60/8XX/YY/ZZ

Small Size (28W)/Large Size (38W/60W/80W/60SW/100SW)

Excellent thermal design, uniform and consistent color. Long life LED chip, shatter-resistant glass, 1-10V dimming. 50,000 hours rated average life.

Product data

General Information

Light source replaceable	NO
Number of gear units	1
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Optical cover/lens type	
Luminaire light beam spread	F.Throw
Sensor socket	
Cable length	Cable 0.3m without plug
Protection class IEC	
Certifications	cETLus, cULus, FCC, DLC5.1 Premium
Lifetime (hour)	50000
EU RoHS compliant	Yes

Light source engine type	LED

Operating and Electrical

Input voltage	100-277/100-347
Input frequency	50/60Hz
Current	0.5A(120-277V/120-347V)
THD	<20%
Power factor (min)	0.9

Mechanical and Housing

Housing material	Aluminum
Reflector material	
Optical cover/lens material	Glass
Optical cover/lens finish	Clear
Product dimensions mm	362.85*190.8*232.7
Product dimensions (inch)	10.35*7.52*9.17
Product color	Bronze/Black/White

Approval and Application

Ingress protection code	IP65
Mech.impact protection code	

Initial Performance (IEC Compliant)

Light output	9000lm
Luminous flux to lerance	+/-10%
Efficacy	150
Init.Corr.Color Temperature	80
Init.Color Rendering Index	80
Initial input power	60W
Power consumotion tolerance	+/-10%

Application Conditions

Ambient temperature range	-30℃-50℃
Dimming	0-10V

Logistical Data

Order product name	WPT05/60/8XX/YY/ZZ
Net weight (piece)	13.45lbs/6.1kgs
Gross weight (piece)	15.43lbs/7kgs
Packaging dimensions (mm)	375*275*275
Packaging dimensions (inch)	14.76*10.83*10.83
Packaging unit (piece)	1


Volumen (m³)	0.028
Volumen (ft³)	0.99


Application

Security lighting Wall lighting Parking lot lighting Entryway lighting

Perimeter lighting Hotel Lighting

Light Distribution & Spectrum





ZEUS V/L

Dimensional drawing



ZEUS V-L

Accessories

Material	Description
Anti-Glare Shield	Anti-glare shield for wall pack series, with white/black/brozen finish.
Wire Guard	Ffor wall pack series
Photecell	Electronic photocontrol
Motion Sensor	Electronic sensor
Emergency Driver	For emergency lighting

Plusrite does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Plusrite. Plusrite is registered.

www.plusrite.com