



# ZEUS V SPECIFICATION

WPT05/60SW/8S3/YY/ZZ

Small Size (28W)/Large Size (38W/60W/80W/60SW/100SW)

Excellent thermal design, uniform and consistent color. Long life LED chip, shatter-resistant glass, 1-10V dimming.  
50,000 hours rated average life.

## Product data

---

### General Information

Light source replaceable	NO
Number of gear units	1
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Optical cover/lens type	-
Luminaire light beam spread	F.Throw
Sensor socket	-
Cable length	Cable 0.3m without plug
Protection class IEC	-
Certifications	cETLus, cULus, FCC, DLC5.1 Premium
Lifetime (hour)	50000
EU RoHS compliant	Yes

Light source engine type	LED
--------------------------	-----

## Operating and Electrical

Input voltage	100-277/100-347
Input frequency	50/60Hz
Current	0.5A(120-277V/120-347V)
THD	<20%
Power factor (min)	0.9

## Mechanical and Housing

Housing material	Aluminum
Reflector material	-
Optical cover/lens material	Glass
Optical cover/lens finish	Clear
Product dimensions mm	362.85*190.8*232.7
Product dimensions (inch)	10.35*7.52*9.17
Product color	Bronze/Black/White

## Approval and Application

Ingress protection code	IP65
Mech.impact protection code	

## Initial Performance (IEC Compliant)

Light output	4200lm-28W/5700lm-38W/9000lm-60W
Luminous flux tolerance	+/-10%
Efficacy	150
Init.Corr.Color Temperature	80
Init.Color Rendering Index	80
Initial input power	28/38/60W
Power consumption tolerance	+/-10%

## Application Conditions

Ambient temperature range	-30°C-50°C
Dimming	0-10V

## Logistical Data

Order product name	WPT05/60SW/8S3/YY/ZZ
Net weight (piece)	13.45lbs/6.1kgs
Gross weight (piece)	15.43lbs/7kgs
Packaging dimensions (mm)	375*275*275
Packaging dimensions (inch)	14.76*10.83*10.83
Packaging unit (piece)	1

Volumen (m <sup>3</sup> )	0.028
Volumen (ft <sup>3</sup> )	0.99

## Application



Security lighting  
Perimeter lighting

Wall lighting  
Hotel Lighting


Parking lot lighting

Entryway lighting

## Light Distribution & Spectrum







## Dimensional drawing



ZEUS V-L

## Accessories

Material	Description
 Anti-Glare Shield	Anti-glare shield for wall pack series, with white/black/brozen finish.
 Wire Guard	Ffor wall pack series
 Photocell	Electronic photocontrol
 Motion Sensor	Electronic sensor
Emergency Driver	For emergency lighting