


# Product Engineering Spec


Product Spec			
Category	Dual Head Security light	Picture	
Item #	DSECW20-BR/8CCT3/YY/SR		
Mounting	Wall Mount		
Housing color	BK/WH/DB/BZ		
Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	20	Lumen (lm)	1640 (3000k) 1900 (4000k) 1700 (5000k)
Tested Wattage (W)	20	Efficacy(lm/w)	82 (3000k) 95 (4000k) 85 (5000k)
Input Voltage (V)	120	CRI	80
Voltage Frequency (Hz)	50/60Hz	CCT (K)	Selectable 3000/4000/5000K
Input Current (A)	0.18	Beam Angle (°)	50°
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	-	Operating Temperature	-40°C~50°C
Surge protect level	2KV	Storage Temperature	-40°C~60°C
Dimmable	/	IP rating	IP65
THD	<20%	Rated Life	50000 hours
LED chip	Bridgelux 3030	Warranty	5 years
Driver	Plusrite		
Product Dimensions		Suggested Accessory	
Weight (lbs.)	4.6		
Height (in)	8.89		
Length (in)	8.11		
Width (in)	6.32		
Mounting Height (in)			
Cable Length(in)			
Qualifications			
UL/ETL	cETLus	LM79	√
Energy Star	√	LM80	√
DLC		IES File	√
CEC		FDA	
JAS		NEMA	
FCC		Dimmer List	
ROHS	√		
Comments:			