



DRAGONFLY III SPECIFICATION

BLR03/60/SW/8S3/YY/PHO

Excellent thermal design, photocell sensor included; Uniform and consistent color, universal voltage:100-277V; 5000 hours rated average life.

Product data

General Information

Light source replaceable	NO
Number of gear units	1
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Optical cover/lens type	
Luminaire light beam spread	Flood
Sensor socket	
Cable length	Cable 0.3m without plug
Protection class IEC	
Certifications	cETLus, DLC5.1 Premium
Lifetime (hour)	50000
EU RoHS compliant	Yes

Light source engine type	I FD
-9	

Operating and Electrical

Input voltage	100-277
Input frequency	50/60Hz
Current	0.6A
THD	<20%
Power factor (min)	0.9

Mechanical and Housing

Housing material	Aluminum
Reflector material	
Optical cover/lens material	Glass
Optical cover/lens finish	Clear
Product dimensions mm	286*70*115
Product dimensions (inch)	11.26*2.76*4.53
Product color	Bronze/Black/White

Approval and Application

Ingress protection code	20
Mech.impact protection code	

Initial Performance (IEC Compliant)

Light output	4500lm-30W/6750lm-45W/9000lm-60W
Luminous flux to lerance	+/-10%
Efficacy	150
Init.Corr.Color Temperature	3CCT
Init.Color Rendering Index	80
Initial input power	30W/45W/60W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	-30°C-50°C
Dimming	0-10V

Logistical Data


Order product name	BLR03/60/SW/8S3/YY/PHO
Net weight (piece)	1.15kgs/2.54lbs
Gross weight (piece)	1.4kgs/3.09lbs
Packaging dimensions (mm)	293*115*215
Packaging dimensions (inch)	11.54*4.53*8.46
Packaging unit (piece)	1

Volumen (m ³)	0.007
Volumen (ft³)	0.25

Application


Security lighting Entryway lighting Perimeter lighting Pathway lighting

Light Distribution & Spectrum



Flood(100 DEG)

Dimensional drawing



Plusrite does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Plusrite. Plusrite is registered.