

SPECIFICATION

GLZJ90W

Our new products have high efficiency, uniform and consistent color, a longer design, a variety of installation methods to meet the needs of different places, beautiful at the same time, with a special lens design that can reduce light to the back side.

Product data

General Information

Light source replaceable	No
Number of gear units	1
Driver/power unit/transformer	Power supply unit
Driver included	No
Optic type	Two sides
Optical cover/lens type	PC Cover
Luminaire light beam spread	-
Sensor socket	-
Cable length	Cable with Male/female connector
Protection class IEC	Safety class I
Certifications	CE
Lifetime (hour)	50,000h
EU RoHS compliant	Yes
Light source engine type	LED

Operating and Electrical

Input voltage	220-400V
Input frequency	50 or 60Hz
Input current	0.26A@380V
THD	<20%
Power factor	>0.9

Mechanical and Housing

Housing material	Aluminum
Reflector material	-
Optical cover/lens material	PC
Optical cover/lens finish	Clear
Product dimensions	2500*70*90mm
Product color	Silver

Approval and Application

Ingress protection code	IP66
Mech.impact protection code	-

Initial Performance (IEC Compliant)

Typical photon flux (umol/s)	270
Photon flux tolerance	+/-10%
Efficacy	3
Init.Corr.Color Temperature	-
Init.Color Rendering Index	-
Initial input power	90W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	0 to +40°C
Dimming	No



Logistical Data

Order product name	GLZJ01/90/400/360° /SL
Net weight (piece)	3.6kg
Gross weight (piece)	-
Packaging dimensions	-
Packaging unit (piece)	-
Volumen	-


Application

© Greenhouse

Light Distribution & Spectrum



Dimensional drawing



Accessories

Material	Description
 Mounting bracket	stainless steel

Plusrite does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Plusrite. Plusrite is registered.

www.plusrite.com