



NESS SPECIFICATION

ALT01/35/8XX/YY

Classic architectural lines. Universal dimming driver (0-10V). 50,000-Hour LED lifespan. Sleek, contemporary, architectural-grade design.

Product data

General Information

Light source replaceable	NO
Number of gear units	1
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Optical cover/lens type	
Luminaire light beam spread	Parking Garage
Sensor socket	
Cable length	Cable 0.3m without plug
Protection class IEC	
Certifications	cETLus/FCC/DLC5.0 Premium
Lifetime (hour)	50,000H
EU RoHS compliant	Yes

Light source engine type	LED

Operating and Electrical

Input voltage	120-277V
Input frequency	50-60Hz
Current	0.4A
THD	<20%
Power factor (min)	0.9

Mechanical and Housing

Housing material	Aluminum
Reflector material	
Optical cover/lens material	Glass
Optical cover/lens finish	Clear
Product dimensions mm	570*140*400
Product dimensions (inch)	22.44*5.51*15.75
Product color	Bronze/Black/White

Approval and Application

Ingress protection code	IP65
Mech.impact protection code	IK08

Initial Performance (IEC Compliant)

Light output	4200lm
Luminous flux to lerance	+/-10%
Efficacy	120lm/w
Init.Corr.Color Temperature	3000K/4000K/5000K
Init.Color Rendering Index	80
Initial input power	35W
Power consumotion tolerance	+/-10%

Application Conditions

Ambient temperature range	-40 to +50℃
Dimming	0-10V

Logistical Data


Order product name	ALT01/35/8XX/YY
Net weight (piece)	7.13kg/15.72lbs
Gross weight (piece)	8.1kg/17.86lbs
Packaging dimensions (mm)	415*415*255
Packaging dimensions (inch)	16.34*16.34*10.04
Packaging unit (piece)	1

Volumen (m³)	0.44
Volumen (ft³)	15.54

Application


Landscape lighting Pathway lighting Perimeter lighting Entryway lighting

Light Distribution & Spectrum



Parking Garage

Dimensional drawing



POST TOP

Accessories

Material	Description
Photecell	Electronic photocontrol

Plusrite does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Plusrite. Plusrite is registered.