



DRUM II SPECIFICATION

ALB03/18/SW/8S3/RLV/YY

Excellent thermal design; uniform and consistent color; universal voltage 120-277V; LM-80 L90 LED chips; operating temp: -40°C~50°C ; different head style available; dimming 0-10V.

Product data

General Information

Light source replaceable	NO
Number of gear units	1
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Optical cover/lens type	-
Luminaire light beam spread	360°
Sensor socket	-
Cable length	Cable 0.3m without plug
Protection class IEC	-
Certifications	cETLus, DLC 5.1 STD
Lifetime (hour)	50000
EU RoHS compliant	Yes

Light source engine type	LED
--------------------------	-----

Operating and Electrical

Input voltage	120-277V/120Vac
Input frequency	50/60Hz
Current	0.16A
THD	<20%
Power factor (min)	0.9

Mechanical and Housing

Housing material	Aluminum
Reflector material	-
Optical cover/lens material	PC
Optical cover/lens finish	Clear/Frost
Product dimensions mm	Ø140.5*1040
Product dimensions (inch)	Ø5.5*40.95
Product color	Black

Approval and Application

Ingress protection code	65
Mech.impact protection code	-

Initial Performance (IEC Compliant)

Light output	1350
Luminous flux tolerance	+/-10%
Efficacy	65/75/83/105/110lm/w
Init.Corr.Color Temperature	3CCT Selectable
Init.Color Rendering Index	80
Initial input power	18
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	-40°C-50°C
Dimming	0-10V

Logistical Data

Order product name	ALB03/18/SW/8S3/RLV/YY
Net weight (piece)	5.03kg/11.09lbs
Gross weight (piece)	5.98kg/12.99lbs
Packaging dimensions (mm)	165*165*1190
Packaging dimensions (inch)	6.5*6.5*46.85
Packaging unit (piece)	1

Volumen (m ³)	0.03
Volumen (ft ³)	1.06

Application


Landscape Lighting

Perimeter Lighting

Perimeter Lighting

Entryway Lighting

Dimensional drawing



DRUM II/1

Plusrite does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Plusrite. Plusrite is registered.